

BAUER PREMIUM LINE

COMPRESSORS FOR SPORTS & SAFETY APPLICATIONS



SPORTS & SAFETY



PROFI LINE II

MOBILE ALL-ROUNDERS FOR PROFESSIONAL APPLICATIONS

FEATURES

- › **Tough and rugged, with extremely durable drive unit for short-term operation and continuous service**
- › **Long service life and durability: three- and four-stage design and industrial roller bearings ensure long operating life**
- › **Reliable lubrication: with generously dimensioned low-pressure oil pump**

CAPITANO

The CAPITANO 140 by BAUER KOMPRESSOREN has been developed specifically for advanced professional applications. Incredible durability, compact dimensions and low weight count here in equal measure.

Furthermore, the first stage and the high-pressure final stage of the CAPITANO 140 feature virtually wear-free piston rings made from a new high-tech plastic.

A vibration-reducing motor base design optimises smooth running.

- › **140 l/min**
- › **225 or 330 bar**
- › **3 kW (4 kW petrol version)**
- › **Available with three-phase motor or petrol engine**

OPTIONAL FEATURES (SELECTION)

- › Additional filling device for 225 or 330 bar
- › Switchover device for 330/225 bar
- › Larger P 31 Purification System for extended filter cartridge life
- › B-TIMER filter cartridge lifetime monitoring system
- › Automatic condensate drain including automatic shutoff when final pressure is reached
- › Crash frame and handles (required for accommodating system accessories)
- › Trolley



CAPITANO 140 with petrol engine and trolley

TECHNICAL DATA

Type	Charging Rate ¹		Operating Pressure max.		Purification System	Number of Stages	Speed	Drive and Motor Power		Net Weight approx.	Dimensions L x W x H
	l/min	cfm	bar	psig				Motor	kW		
CAPITANO 140-B	140	5	350	5000	P 21	3	1,300	Petrol engine 4-stroke	4.0	95	115 x 59 x 55
CAPITANO 140-E	140	5	350	5000	P 21	3	1,300	Three-phase 400 V, 50 Hz ²	3.0	102	115 x 59 x 55
MARINER 200-B	200	7	350	5000	P 21	3	1,250	Petrol engine 4-stroke	5.9	115	125 x 59 x 63
MARINER 200-E	200	7	350	5000	P 21	3	1,250	Three-phase 400 V, 50 Hz ²	4.0	115	125 x 59 x 63
MARINER 250-B	250	9	350	5000	P 31	3	1,450	Petrol engine 4-stroke	6.6	120	125 x 59 x 63
MARINER 250-E	250	9	350	5000	P 31	3	1,450	Three-phase 400 V, 50 Hz ²	5.5	135	125 x 59 x 63
MARINER 320-B	320	11.5	350	5000	P 31	4	1,450	Petrol engine 4-stroke	8.8	138	130 x 64 x 70
MARINER 320-E	320	11.5	350	5000	P 31	4	1,450	Three-phase 400 V, 50 Hz ²	7.5	154	130 x 64 x 70

1 Measured by cylinder filling (10 l) from 0 - 200 bar / 2900 psig, ± 5%.

2 Plug dimension: 16 A.

PROFI-LINE II 420 BAR

Type	Charging Rate ¹		Operating Pressure max.		Purification System	Number of Stages	Speed	Drive and Motor Power		Net Weight approx.	Dimensions L x W x H
	l/min	cfm	bar	psig				Motor	kW		
MARINER 320-B	320	11.5	420	6000	P 41/420	4	1,450	Petrol engine 4-stroke	8.8	138	130 x 64 x 70
MARINER 320-E	320	11.5	420	6000	P 41/420	4	1,450	Three-phase 400 V, 50 Hz ²	7.5	154	130 x 64 x 70

1 Measured by cylinder filling (10 l) from 0 to 200 bar, ± 5%.

2 Plug dimension: 16 A.

PROFI-LINE II DIESEL

Type	Charging Rate ¹		Operating Pressure max.		Purification System	Number of Stages	Speed	Drive and Motor Power		Net Weight approx.	Dimensions L x W x H
	l/min	cfm	bar	psig				Motor	kW		
CAPITANO II-D	140	5	330	4780	P 21	3	1,300	Diesel engine	5.0	158	110 x 58 x 62.5
MARINER II-D	170	6	330	4780	P 21	3	1,130	Diesel engine	5.0	158	110 x 58 x 62.5

1 Measured by cylinder filling (10 l) from 0 to 200 bar, ± 5%.



**ARE YOU INTERESTED IN OUR
PRODUCTS?**

**CONTACT US – WE ARE HAPPY TO PROVIDE
INFORMATION AND ASSISTANCE:**

BAUER KOMPRESSOREN GmbH
Stäblistr. 8
81477 Munich, Germany
Tel. +49 (0) 89 78049-0
Fax +49 (0) 89 78049-167
info@bauer-kompressoren.de
bauer-kompressoren.de



BAUER PREMIUM LINE EN
N39891
12.2017

Subject to technical change without notice